

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
3 February 2005 (03.02.2005)

PCT

(10) International Publication Number
WO 2005/009640 A1

(51) International Patent Classification⁷: **B21C 47/04**,
47/18, 47/26, B21B 1/46

(21) International Application Number:
PCT/IT2004/000378

(22) International Filing Date: 8 July 2004 (08.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
MI2003 A 001546 28 July 2003 (28.07.2003) IT

(71) Applicant and

(72) Inventor: ARVEDI, Giovanni [IT/IT]; Via Mercatello,
26, I-26100 Cremona CR (IT).


(74) Agent: ADORNO, Silvano; Società Italiana Brevetti
S.p.A., Via Carducci, 8, I-20123 Milano (IT).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: THERMO-ELECTROMECHANICAL PROCESS AND SYSTEM FOR COILING AND UNCOILING AN IN-LINE
HOT ROLLED PRE-STRIP FROM THIN SLAB CONTINUOUS CASTING



(57) Abstract: A system and the relevant
thermo-electromechanical process with
two superimposed devices (A) able to coil
and uncoil a pre-strip (a) by reversing their
positions, provided with outer (4) and inner
(7) burners to respectively equalize and
optimise the temperature along the whole
pre-strip by means of special algorithms of
the control software, suited to also control
the speed, acceleration and deceleration,
both in the coiling and uncoiling step, of
the chuck (6) up to the advanced stop during
coiling to let a segment of tail (c) of the
pre-strip out of the device (A). A particular
structure of the chuck (6) is also described.

WO 2005/009640 A1



Published:

- with international search report
- with amended claims

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

2/pets
JC20 Rec'd PCT/PTO 25 OCT 2009

THERMO-ELECTROMECHANICAL PROCESS AND SYSTEM FOR
COILING AND UNCOILING AN IN-LINE HOT ROLLED PRE-STRIP FROM
THIN SLAB CONTINUOUS CASTING

5 The present invention relates to a process and related system formed by a double superimposed electromechanical device, heated by gas burners and adapted to coil and uncoil at a controlled speed pre-strips of steel fed from a thin slab casting apparatus with in-line hot rolling ("cast rolling"), able to connect in a controlled way such a step with the following one of final rolling, being separated
10 therefrom by different working speeds.

 It is known in manufacturing plants for flat steel products, to use apparatuses for temporarily coiling the products ahead of the hot finishing rolling mill in order to separate the low velocity portion connected to the continuous casting from the finishing rolling mill that functions on the contrary at higher speed, so as to form
15 coils usable as a store stock. A typical apparatus is the so-called "coil box" developed by Selco and employed both in conventional plants and for the so-called "mini-mills" using the thin slab technology.

 This system is substantially formed by a series of input rolls for bending and causing the flat product to be coiled, as well as by powered rolls suitable to impart
20 to the product the required rotation for the formation of the coil, freely occurring without any central chuck and without any protection shell. The used apparatus has however some disadvantages, the first of which is the impossibility of coiling thin slabs or pre-strips having a thickness lower than 15 mm, the danger being the collapsing of the coil on itself which would prevent the subsequent uncoiling
25 thereof. Furthermore the absence of an outer shell involves temperature loss problems due to irradiation and non homogenous temperature, which make difficult the achievement of good quality products, from the point of view of both their geometry and mechanical properties.

 It is true that patent US 4,703,640 attempts to solve these problems by
30 providing an embedding and the possibility of using a conventional chuck, while DE 4013582 provides a possible solution with two coilers, each of them

embedded in its own shell and mutually superimposed, but both solutions have technical disadvantages. Disadvantages which are due to the presence of heads and tails, unavoidably colder than the central portion of the strip, that entail problems in the subsequent rolling process particularly in the case of thin and
5 ultra-thin gauges, thus giving rise in particular to:

- the impossibility of controlling the pre-strip temperature as the apparatus have no heating systems, and accordingly the impossibility to produce strips with limited tolerances or particular characteristics such as thermo-mechanical steels of the dual phase or HSLA type;
- 10 - the lack of control of the coiling/uncoiling speed of the pre-strip, and therefore the impossibility to produce thin and ultra-thin strips with strict tolerances owing to the stretches ensuing from a non-controlled unwinding;
- problems for the so-called "refusals" of the rolling stands to accept a material showing at the head zone, in a length of few centimetres,
15 temperature differences of some tens of degrees;
- out-of-tolerance in the first and last strip lengths (tens of meters), particularly in the production of thin and ultra-thin strips;
- incorrect positioning or "out-of-table" of the head with a consequent warping of the first strip meters, with consequent problems of strip stability
20 and coiling;
- incorrect positioning or "out-of-table" of the tail with consequent damages of the strip and rolling rolls.

WO 96/32509 provides for two superimposed steel strip coiling and uncoiling devices having induction heaters only on the strip exit guides to the
25 outside, made as roller paths, without any possibility of optimising and making uniform the temperature along the whole strip.

Still with reference to the aforesaid patents, it is possible to note that to avoid any cooling of the strip tail, the latter would have to be coiled internally, but this implies remarkable difficulties to withdraw the same, otherwise the device
30 should have a wide opening, condition that would cause remarkable temperature losses; for these reasons such apparatus have no practical applications.

Starting from the described problems and disadvantages of the prior art, the present invention aims at improving a device for coiling/uncoiling a pre-strip from an in-line casting and rolling system, while ensuring to said product a high level of heat uniformity and an electronic control of the coiling/uncoiling speed, regarded as essential in order to obtain a final product with strict geometric tolerances and uniform mechanical properties.

This object is achieved according to the invention by means of an electromechanical system having the features as stated in claim 1, and a process according to claim 4.

Further objects, advantages and features of the system according to the present invention, as well as the relevant process, will be clear from the following description of a preferred embodiment thereof with reference to the attached drawings wherein:

Figure 1 shows a sectional view of said embodiment in which the two devices forming the inventive system are superimposed to each other;

Figure 2 shows a cross-sectional schematic view of the central chuck of each single coiling/uncoiling device of the system; and

Figures 3 and 4 respectively show a frontal view and a sectional view along line IV-IV thereof of a preferred embodiment for joining by fitting the chuck central body to the lateral segments.

Referring now to Fig. 1, there is shown the configuration according to the invention in which both superimposed coiling/uncoiling devices A of pre-strip are allowed to alternately rotate about their own horizontal axis in clockwise and counter-clockwise direction at an angle comprised between 40 and 120°, in order to ensure continuity between the in-line casting and hot rolling step and the final rolling. Each one of both devices A is separately heated by suitable burners 4 of natural gas and is independently operated by means of a special software able to control both the coiling/uncoiling speed and the heating temperature. Furthermore, in order to ensure a quick insertion to the descaling systems and subsequently to the finishing rolling mill placed downstream, the tail c of the pre-strip is intentionally let come out from the protecting envelope by a length comprised

between 0 and 800 mm and, prior to the final rolling, it is heated by said burners 4 (blown out during the coiling step) required to ensure the thermal uniformity with the remaining pre-strip **a** being coiled and heated within device A.

It is to be noted that the coiling/uncoiling device A can preferably include subsidiary equipments to aid the input or output of the pre-strip at the openings of the outer envelope.

To this end, as a preferred but non-limiting solution, there could be adopted the one of the prior art disclosed in patent IT 1245612, in which the strips are directed inwardly and outwardly by a couple of rolls 2 placed at the inlet of devices A and supported during the coiling step by a plate 3 that is located within the protecting shell to aid the insertion thereof in a coiling chuck 6.

To this end, as preferred solution, each coiling device A comprises within an insulated envelope A' a fixed, not expandable chuck 6, in whose structure a slot 5 for the insertion of head **b** of the pre-strip is present as well as second burners 7 to equalize the temperature of strip **a** both during the coiling and uncoiling step. The combustion of burners 7 is controlled by a specific software according to an algorithm which controls the relevant stoichiometric ratio intentionally unbalanced with an excess of gas (reducing combustion) in order to aid the formation of an oxide easily removable by the descaling devices placed downstream before the final rolling. The control software of burners 7 is also provided with an algorithm able to increase or decrease the flow rate of the burners to obtain a steady temperature between the leading end and trailing end of the strip both during the coiling and uncoiling step, or as a function of the kind of steel of pre-strip **a** and the properties the finished product must have.

The envelope A' has an opening defined by the couple of rollers 2 that in the coiling step is oriented upstream with respect to the rolling direction for receiving the pre-strip **a** to be coiled (Fig. 1 – lower device), while in the uncoiling step is oriented downstream when the pre-strip uncoils for being directed to the final rolling (Fig. 1 – upper device). This operation is made possible because the whole device A can rotate on itself by an angle comprised between 40 and 120° about its own axis, so as to allow the correct alignment of the opening defined by rollers 2

with the upstream and downstream portions, respectively for the lower and upper device, of the line in which it is inserted.

Suitable control means cause the rotation of a deflecting element or pass-line 1 till it is oriented towards the opening of rollers 2, so as to guide pre-strip a
5 towards device A (the lower one in Fig. 1), and once fed forward by rollers 2, to enter and mesh in slot 5 of chuck 6, that by rotating clockwise as shown by the arrow, causes coiling thereof about itself.

At the opening between rollers 2, in uncoiling condition (upper device), after the burners 4 have heated the tail end c of the strip, the deflecting element is
10 oriented upwards to support said tail and aid the fitting thereof into the downstream devices, and thus towards the final rolling. Obviously the deflecting or coiling-helping element 1 as well as the uncoiling-helping element 1' of the pre-strip could be made in any other equivalent and aim-suited way.

With a view to avoid undesired difficulties between the coiling and
15 uncoiling steps in the upper and lower devices, a special algorithm of the controlling software of devices A speeds up the coiling step of pre-strip a when this is cut by shears (not shown) placed at the end of the in-line casting and hot rolling system (cast-rolling), so as to create the required room for ensuring the right positioning of helping element 1.

20 The controlling software comprises also an algorithm which allows to slow down the coiling step when this is going to end and the distance from the following strip is enough to ensure the coiling thereof, thus enhancing the heating of tail c that will remain out of device A and rollers 2.

A preferred embodiment of chuck 6 to be used for the device A is shown in
25 greater detail in Figs. 2-4. With reference to Fig. 2, there is seen the hollow central shaft 6.1 of the chuck within a central body 6.2; at the sides thereof two steel segments 6.3 are provided, appropriately lightened as the same central body 6.2. The shaft 6.1 is cooled with water flowing in the axial hole 6.4 and has outside an insulating layer 6.5, which by limiting the passage of heat between the shaft and
30 central body 6.2 minimizes the cooling of the first length b of the coiling strip which corresponds to the uncoiling tail for the subsequent rolling, as well as of the

inner part of device A.

Such a preferred embodiment provides that the central body 6.2 is fixedly joined to lateral segments 6.3 by means of shaped claws 6.6, 6.6' which engage with spacers 6.7 inserted for allowing the assembly without the aid of tie rods as
5 required in conventional embodiments. These latter were particularly unreliable owing to the unavoidable failures occurring as a consequence of stresses at the high working temperatures, and the replacement thereof involved each time a stopping period of two or more days.

The particular embodiment shown in Figures 3 and 4 has not only the
10 purpose of increasing the reliability of the chuck and its easy feasibility, but also of being able to hold up the counterpull between said device and the downstream devices, namely between the descaler and finishing rolling mill.

CLAIMS

1. A thermo-electromechanical system comprising two mutually superimposed devices (A) in respective fireproof shells (A'), able to coil, on a relevant central chuck (6) by means of couples of input and output rolls (2), a pre-strip (a) with a thickness comprised between 30 and 8 mm from a roughing mill directly connected to a casting line for thin slabs, and subsequently to rotate on themselves and uncoil said pre-strip for allowing the inlet to the following descender and finishing rolling mill, characterized in that
- 10 - said devices (A) have outer (4) and inner (7) burners of natural gas;
 - said inner burners (7) are able to optimise the temperature of the pre-strip (a) to be entered into the finishing roller mill, by means of a suitable control software also provided with an algorithm able to change the flow rate of burners to achieve automatically a steady temperature between the leading and trailing ends of the strip both when coiled and uncoiled or as a function of the kind of steel of pre-strip (a) and the properties to be obtained on the finished product;
 - 15 - said outer burners (4) are able to homogenize through a special control software the temperature of pre-strip (a) on the whole length thereof from the coiled core to a terminal tail portion (c), which remains outside, whereby the complete uniformity of the mechanical and geometric characteristics of the final product, responsive to temperature changes, is ensured;
 - 20 - actuating means are provided for the rotation of chucks (6) of upper and lower devices (A) both when coiled and uncoiled under control of special algorithms of the controlling software to speed up or slow down the coiling of pre-strip (a);
 - 25 - control means are provided for the speed of said pre-strip (a) both when being coiled and uncoiled, consisting of a special process software in order to avoid stretches or compressions of pre-strip, such as to jeopardize the geometric quality of the final product; and
 - 30

- means are provided for operating the stop of the chuck (6) by leaving said tail end (c) of pre-strip upon coiling at the outside of said devices (A) and said couples of rolls (2) for a length comprised between 0 and 800 mm, thus making easier, in the subsequent uncoiling, its entering to the following descaling and final rolling up to the finishing roll train.

2. A system according to claim 1, characterized in that, downstream of the in-line casting and hot rolling step, a shear cuts the pre-strip, and a first one of said controlling software algorithms of devices (A) speeds up the coiling thereof so as to create the required room to ensure the correct positioning of a helping device (1) to receive on the coiling device (A) the following strip.

3. A system according to claim 1, characterized by comprising a second algorithm of the control software suitable to allow the slowing down of the coiling step, immediately before its completion, when the distance from the following strip is sufficient to ensure its coiling, thus assisting the heating of the terminal portion (c) left outside the device (A) and rolls (2).

4. A system according to claim 1, characterized in that said chuck (6) on which the pre-strip (a) is wound comprises a drum formed of a central body (6.2) with central shaft (6.1) and side segments (6.3) held together by mutually fitted parts (6.6, 6.7, 6.6', 6.7') without the aid of bolts.

5. A system according to claim 4, characterized in that said chuck (6) is thermally insulated from the central shaft (6.1) on which it is mounted, the latter being hollow with an axial hole (6.4) for the cooling water, thus avoiding that the head and outgoing tail of the entering pre-strip (b) undergo such cooling as to jeopardize its capability to be rolled.

6. A process for the thermo-mechanical treatment of a pre-strip with a thickness comprised between 30 and 8 mm from a roughing mill directly connected to a casting line for thin slabs, comprising the coiling and subsequent uncoiling thereof to allow its forwarding to the finishing rolling, characterized by further comprising:

- the heating by burning natural gas, controlled by a special software of the pre-strip during the coiling and uncoiling steps, inside and outside the

coiling devices;

- the control, through special algorithms of the process software, of the coiling step for the relevant speeding up or slowing down;
- the control, through a special process software, of the speed of pre-strip during the coiling and uncoiling step.

5

7. A process according to claim 6, characterized in that the combustion for heating the pre-strip within the coiling device occurs with an excess of gas with respect to the stoichiometric ratio in order to assist in a reducing environment the formation of a surface oxide easily removable as a scale

10

in a subsequent descaling step.

AMENDED CLAIMS

[Received by the International Bureau on 10 December 2004 (10.12.04) ; original claims 1-6 and 7 amended ; remaining claims unchanged]

1. A thermo-electromechanical system comprising two mutually superimposed devices (A) in respective fireproof shells (A') with inner burners (7)
- 5 of natural gas, able to coil, on a relevant central chuck (6) by means of couples of input and output rolls (2), a pre-strip (a) with a thickness comprised between 30 and 8 mm from a roughing mill directly connected to a casting line for thin slabs, and subsequently to rotate on themselves and uncoil said pre-strip for allowing the inlet to the following descender and finishing rolling mill, characterized in that
- 10 - said devices (A) are also provided with outer (4) burners;
- said inner burners (7) are able to optimise the temperature of the pre-strip (a) to be entered into the finishing roller mill, by means of a suitable control software also provided with an algorithm able to change the flow rate of burners to achieve automatically a steady temperature between the leading
- 15 and trailing ends of the strip both when coiled and uncoiled or as a function of the kind of steel of pre-strip (a) and the properties to be obtained on the finished product;
- said outer burners (4) are able to homogenize through a special control software the temperature of pre-strip (a) on the whole length thereof from
- 20 the coiled core to a terminal tail portion (c), which remains outside, whereby the complete uniformity of the mechanical and geometric characteristics of the final product, responsive to temperature changes, is ensured;
- actuating means are provided for the rotation of chucks (6) of upper and
- 25 lower devices (A) both when coiled and uncoiled under control of special algorithms of the controlling software to speed up or slow down the coiling of pre-strip (a);
- control means are provided for the speed of said pre-strip (a) both when
- 30 being coiled and uncoiled, consisting of a special process software in order to avoid stretches or compressions of pre-strip, such as to jeopardize the geometric quality of the final product; and

JC20 Rec'd PCT/PTO 25 OCT 2009

- means are provided for operating the stop of the chuck (6) by leaving said tail end (c) of pre-strip upon coiling at the outside of said devices (A) and said couples of rolls (2) for a length comprised between 0 and 800 mm, thus making easier, in the subsequent uncoiling, its entering to the following descaling and final rolling up to the finishing roll train.

2. A system according to claim 1, characterized in that, downstream of the in-line casting and hot rolling step, a shear cuts the pre-strip, and a first one of said controlling software algorithms of devices (A) speeds up the coiling thereof so as to create the required room to ensure the correct positioning of a helping device (1) to receive on the coiling device (A) the following strip.

3. A system according to claim 1, characterized by comprising a second algorithm of the control software suitable to allow the slowing down of the coiling step, immediately before its completion, when the distance from the following strip is sufficient to ensure its coiling, thus assisting the heating of the terminal portion (c) left outside the device (A) and rolls (2).

4. A system according to claim 1, characterized in that said chuck (6) on which the pre-strip (a) is wound comprises a drum formed of a central body (6.2) with central shaft (6.1) and side segments (6.3) held together by mutually fitted parts (6.6, 6.7, 6.6', 6.7') without the aid of bolts.

5. A system according to claim 4, characterized in that said chuck (6) is thermally insulated from the central shaft (6.1) on which it is mounted, the latter being hollow with an axial hole (6.4) for the cooling water, thus avoiding that the head and outgoing tail of the entering pre-strip (b) undergo such cooling as to jeopardize its capability to be rolled.

6. A process for the thermo-mechanical treatment of a pre-strip (a) with a thickness comprised between 30 and 8 mm from a roughing mill directly connected to a casting line for thin slabs, comprising the coiling and subsequent uncoiling thereof to allow its forwarding to a finishing rolling step, providing for the heating (7) by burning natural gas during the coiling and uncoiling steps inside coiling devices (A), characterized by further comprising:

- an additional heating (4) outside said coiling devices (A), with said inside


heating (7) being controlled by a special software of the pre-strip (a);

- the control, through special algorithms of the process software, of the coiling step for its respective speeding up or slowing down; and
 - the control, through a special process software, of the speed of pre-strip (a)
- 5 during the coiling and uncoiling steps.

7. A process according to claim 6, characterized in that the combustion for heating the pre-strip within the coiling device occurs with an excess of gas with respect to the stoichiometric ratio in order to assist in a reducing environment the formation of a surface oxide easily removable as a scale




10 in a subsequent descaling step.

Fig.1



• •

• •

Fig. 2Fig. 3Fig. 4

JC2D Receipt 25 OCT 2024

THIS PAGE BLANK (USPTO)

INTERNATIONAL SEARCH REPORT

International Application No
T/IT2004/000378

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 B21C47/04 B21C47/18 B21C47/26 B21B1/46

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B21C B21B C21D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	"ISP - THIN SLAB CHALLENGE TO NUCOR" STEEL TIMES, FUEL & METALLURGICAL JOURNALS LTD. LONDON, GB, vol. 221, no. 10, 1 October 1993 (1993-10-01), pages 416,418-419, XP000407075 ISSN: 0039-095X the whole document	1-3,6
A	US 4 630 352 A (GINZBURG VLADIMIR B ET AL) 23 December 1986 (1986-12-23) column 1, line 47 - column 2, line 3 column 2, line 63 - column 3, line 9; figure 1 ----- -/--	1,6

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *Z* document member of the same patent family

Date of the actual completion of the international search

27 October 2004

Date of mailing of the international search report

05/11/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Ritter, F

INTERNATIONAL SEARCH REPORT

national Application No
T/IT2004/000378

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 96/32509 A (VOEST ALPINE IND ANLAGEN ; MOSER FRIEDRICH (AT)) 17 October 1996 (1996-10-17) cited in the application page 2, paragraph 4 - page 3, paragraph 2; claims 1,11; figure 1 -----	1,6
A	DE 40 13 582 C (MANNESMANN AG) 11 July 1991 (1991-07-11) cited in the application the whole document -----	1
A	US 5 195 344 A (MASUDA SADAKAZU ET AL) 23 March 1993 (1993-03-23) column 2, line 51 - column 3, line 56; figure 1 -----	1,6
A	DATABASE WPI Derwent Publications Ltd., London, GB; AN 1986-211068 XP002302848 & SU 1 202 653 A (INST CHERNOI METALLURGII) 7 January 1986 (1986-01-07) abstract -----	1,6
A	DATABASE WPI Derwent Publications Ltd., London, GB; AN 2001-576052 XP002302849 & KR 2001 019 326 A (PO HANG IRON & STEEL) 15 March 2001 (2001-03-15) abstract -----	1,6
A	DE 85 36 151 U (BERGISCHE STAHL-INDUSTRIE) 20 February 1986 (1986-02-20) figure 1 -----	4,5
A	US 4 630 785 A (LANGEDER RUDOLF ET AL) 23 December 1986 (1986-12-23) figures 1,2 -----	4,5
A	DE 30 00 638 A (MECANARBED SA) 31 July 1980 (1980-07-31) page 6, paragraph 3; claim 1 -----	7
A	US 5 690 485 A (MANGHAM WILLIAM J ET AL) 25 November 1997 (1997-11-25) column 1, line 49 - column 2, line 46 -----	7

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

:T/IT2004/000378

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4630352	A	23-12-1986	EP 0177187 A1	09-04-1986
WO 9632509	A	17-10-1996	AT 403169 B	25-11-1997
			AT 64795 A	15-04-1997
			WO 9632509 A1	17-10-1996
			DE 19680225 C1	02-12-1999
			DE 19680225 D2	18-09-1997
			GB 2303691 A ,B	26-02-1997
			JP 10501469 T	10-02-1998
			US 5778716 A	14-07-1998
DE 4013582	C	11-07-1991	DE 4013582 C1	11-07-1991
			IT 1245612 B	29-09-1994
			US 5131134 A	21-07-1992
US 5195344	A	23-03-1993	JP 63220901 A	14-09-1988
			EP 0381756 A1	16-08-1990
			WO 8911348 A1	30-11-1989
SU 1202653	A	07-01-1986	SU 1202653 A1	07-01-1986
KR 2001019326	A	15-03-2001	NONE	
DE 8536151	U	20-02-1986	DE 8536151 U1	20-02-1986
US 4630785	A	23-12-1986	AT 382393 B	25-02-1987
			AT 197284 A	15-07-1986
			CA 1226133 A1	01-09-1987
			DD 233144 A5	19-02-1986
			DE 3560041 D1	12-02-1987
			EP 0166713 A1	02-01-1986
			JP 61017326 A	25-01-1986
			SU 1311605 A3	15-05-1987
DE 3000638	A	31-07-1980	LU 80840 A1	08-08-1980
			DE 3000638 A1	31-07-1980
			FR 2447237 A1	22-08-1980
			IT 1129535 B	04-06-1986
US 5690485	A	25-11-1997	US 5556273 A	17-09-1996

THIS PAGE BLANK (USPTO)